



DEUS RRC PVT. LTD.



Leading manufacturer of SNT Radio Remote Control Systems & other Crane Control Equipments.

- Plot No.4319, G.I.D.C, Vatva, Phase IV, Ahmedabad - 382445, Tel: 079-25841148, E-mail:sales@sntrrc.com
- 120, Acharya Ind. Estate, Tejpal Compound, Andheri-kurla Road, Sakinaka, Mumbai-400 072
Tel. : +91 7506507534 / 9821092946 E-mail: mail@sntrrc.com

DEUS - SNT Current Collector For EOT Crane



Features

- Quick & easy Installation.
- Collector Shoes track Accurately on V Contact Bar.
- Bolted Joint.
- Insulating cover shaped to shed from water and dust & Finger Safe.
- 60 to 400Amps. conductor in same size.
- Requires fewer joints and expansion joints.
- Track Configuration : Straight or Curved.
- Suitable for Indoor / Outdoor Installation

TECHNICAL SPECIFICATION

SAFELINK Current Collectors Data Sheet		
Type	SLCC - 125	SLCC - 250
Current Rating	125A	250A
Collector Movement	± 200 ± 60	± 200 ± 60
Mounting Bracket	25Sqmm bar	25Sqmm bar
Mounting Distance from Conductor contact surface	127mm	127mm
Construction	1 Pole	1 Pole
Spring Loaded Contacts with Springs of non Rusting	Stainless Steel	Stainless Steel
Sintered Copper Shoe	125A	250A
Shoe Holder	Nylon	Nylon
Structure	Metallic	Metallic
Suitable to use on Safelink Conductor System On Straight Track	SFM (100/125/250/315A) SFW (60/100/125/160/250/400A)	SFM (60/100/125/160/250/400/200/315A) SFV (500/800/100A)
On Curved Track	SFM (100/125/250/315A) SFW (60/100/125/160/250/400A)	SFM (60/100/125/160/250/400/200/315A) SFW (60/100/125/160/250/400A)
Higher Currents	Two Collectors in Tandem to be used for higher current requirements and for expansion assemblies	